



TILING FAMILY

TILING



Description

Tiling standstone ceramic porphyre
This product is MONTANA type, Granito 1.
UPEC: U4 P3 E3 C2.
Grey colour (Pantone: Cool Gray 5C).
Pointing in the grey tone of the material.
Double gluing on tiled floor floated.

Sizes

30 x 30 cm. 45 x 45 cm.

CLEANING OPERATION PROCEDURE

· 1st Cleaning (After laying)

TO DO

- To wet the fooring before use of acid solution to impregnate the joints of water in order to avoid their corrosion.
- · Cleaning with a muriatic acide solution (diluted at 10 %) or with dedicated products for this operation (Casalgrande Deterprimo, Nelsen Viacal, Mapei Keranet, Kerakoll Deltaplus,) to remove remaining ciments and glue traces.
- · Large water rinsing, to.

TO NOT DO

- · If joints are not impregnated of water, they will be dissolved by the acid solution, giving a bigger porosity then a joint more difficult to lean et easier to stain.
- To clean only with water: after drying, the tiled floor will seem dull.
- · If the flooring is not largely rinsed with water after « acid » cleaning, ciment milt and glue traces will reappear. Then the 1st cleaning.

CLEANING OPERATION PROCEDURE

Routine cleaning

TO DO

- · Use ammionaque : AJAX, VIGOR, ...
- Respect indicated dilutions on specifications & technical sheets of used products.
- Use where it is possible a singlebrush machine (medium/hard disc). Cleaning tank must be separated of rinsing tank.
- Proceed to an « acid » cleaning per month to remove limestone from rinsing water

TO NOT DO

- This is totally forbidden to use cleaning products composed of saponifying agent (soap, linseed oil like Carolin). Those products make on surface a greasy film taht will keep dirtyness the flooring. More those products are used more it will difficult to remove this film.
- To clean and rinse with the same tank (speaking about sigel-brush machine) is not efficient.
- Clean everytime with an acid solution will destroy joints especially if the rinsing is not done correctly and a couple of times